

(19) World Intellectual Property Organization  
International Bureau



(43) International Publication Date  
18 January 2001 (18.01.2001)


PCT

(10) International Publication Number  
**WO 01/04670 A1**

- (51) International Patent Classification<sup>7</sup>: **G02B 5/28**,  
5/08, H01S 3/08 Optics Division, 2303 Lindbergh Street, Auburn, CA  
95602 (US).
- (21) International Application Number: PCT/GB00/02549 (74) Agent: **TILLBROOK, Christopher, John**; 1 Mill Street,  
Warwick CV34 4HB (GB).
- (22) International Filing Date: 10 July 2000 (10.07.2000)
- (25) Filing Language: English
- (26) Publication Language: English
- (30) Priority Data:  
9916339.6 13 July 1999 (13.07.1999) GB
- (71) Applicant (for all designated States except US): **COHER-  
ENT OPTICS EUROPE LIMITED** [GB/GB]; 27-35  
Ashville Way, Whetstone, Leicestershire LE8 6NU (GB).
- (72) Inventors; and
- (75) Inventors/Applicants (for US only): **BOUCHER, Neil**,  
A. [GB/GB]; Coherent Optics Europe Limited, 27-35  
Ashville Way, Whetstone, Leicestershire LE8 6NU (GB).  
**FISHER, Dennis, G.** [US/US]; Coherent Auburn Group,
- (81) Designated States (national): AE, AL, AM, AT, AU, AZ,  
BA, BB, BG, BR, BY, CA, CH, CN, CR, CU, CZ, DE, DK,  
DM, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL,  
IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU,  
LV, MA, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT,  
RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, TZ, UA,  
UG, US, UZ, VN, YU, ZA, ZW.
- (84) Designated States (regional): ARIPO patent (GH, GM,  
KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZW), Eurasian  
patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European  
patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE,  
IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG,  
CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).
- Published:  
— With international search report.

[Continued on next page]

(54) Title: INDUCED ABSORPTION FILTER (IAF)



(57) Abstract: An optical filter uses a multi-layer, stack of alternating dielectric layers (16, 18) of different refractive indices, a dielectric spacer layer (20) and metal layer (21), to achieve a narrow overall absorption bandwidth, with high reflectance upon either side. A tunable (optical) filter variant uses a dielectric stack and spacer coating of spatially-varying thickness, that is a coating of depth varying, say linearly and/or circularly, according to position across an absorbent layer or substrate, whereby, at different positions on the surface, a different wavelength is absorbed. A tunable laser (35) uses opposed tunable filters (26, 28) bounding a lasing medium (38), such as CO<sub>2</sub> gas, for selective variable stimulated emission of radiation (39).

WO 01/04670 A1